



Alpha-WA

Rotating Arm Type For Heavy & Unstable Load

Description

Ideal machine for heavy or unstable loads. To integrated with power conveyors as fully auto in-line wrapping system.

Equipped with auto film clamp, cut & wiper system makes wrapper ready for next pallet. Automatically complete film wrapping on pallet loads. Provide consistent wrapping and professional looking loads. Productivity increased.

Heavy duty frame made of high steel structure and durable gear bearing rotation, run for longevity and less maintenance.

Soft start, stop & home position prevents load displacement at the beginning & the end.

Safety fence surrounding around rotating machine ensure safety during the wrapping process. Access door with sensors. Disconnect the machine when access door open for maintenance.

Quick connector plug in & out, easy to install. Comprehensively correspondence with variety of applications.

Features

- Auto film clamp, cut wiper system
- Auto sensor for loading height detect
- Durable gear bearing rotation structure
- Rotation soft-start, stop & home position
- Individual control box with HMI touch panel
- Film carriage with power pre-stretch system
- Rotating arm and film carriage speed adjustable

Options

- Top press
- Top sheet dispenser
- Power roller or chain conveyors
- Heat sealing plate (Reinforces film sealed on pallet load)

Specification

Turntable dia. (mm)	3114 (customize)
Wrapping height (mm)	2100 / 2400
Max. pallet weight (kg)	customize
Turntable speed (R.P.M.)	4~15
Film carriage speed (m/min.)	2~5
Film roll I.D. (mm)	φ76x W 500
Power consumption (kW)	1.5
Power supply (50/60Hz)	220/230/380/415/440V,3PH
Dimension (L x W x H mm)	3700 x 4250 x 3500
Machine net weight (kg)	2000
Pre-stretch ratio (50%,100%,150%,200%)	specified.

*Specification subject to change without notice



JIA-IN INDUSTRY CO., LTD.

T +886 4 2359 4966

F +886 4 2359 2449

E info@joinpack.com

www.joinpack.com

