



## A-93

### General Application Bottom Seal Automatic Strapping Machine

#### Description

A-93 is designed for general applications with its reputation since years. Various arch size combination and workability of different strap widths between 9 ~ 15 mm can serve all kinds of packages. Tension range between 15-70 KGs and cycle speed 24 straps/min performed thru AC motor driven.

Available to equip with various unique options to perform advanced functions.

#### Features

- Hinged table top
- Proximity cam switch
- Instant heating system
- Modular arch component
- Weld cooling time adjustable
- Available for both PP& PET strap ( specified)
- Digital regulator in PCB with LED show I/O status

#### Options

- Looping ejector
- Auto loading system
- Short feeding sensor
- Coil end strap ejecting out
- Electronic tension control system
- Stainless steel housing available : **A-93M**

#### Specification

Speed (straps / min)	24
Strap width (mm)	9,12,15 specified
Tension range	15~70kgs
Standard arch (W x H mm)	850 x 600
Motor	AC
Sealing method	Heating element
Table height (mm)	805
Power supply	110/220/230/240V, 50/60Hz, 1PH 220/230/380/415/440V, 50/60Hz, 3PH
Power consumption (kw)	1.0
Layout dimension (L x W x Hmm)	1440 x 600 x 1530

\*Specification subject to change without notice



JIA-IN INDUSTRY CO., LTD.

T +886 4 2359 4966

F +886 4 2359 2449

E info@joinpack.com

www.joinpack.com

